

GRAFFITI REMOVER

T018

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product Code T018

Manufacturer : Selden Research Limited
Staden Lane Business Park, Staden Lane,
Buxton, Derbyshire. SK17 9RZ
United Kingdom

Product Name GRAFFITI REMOVER

Tel : 01298 26226
Fax : 01298 26540
Email : sales@selden.co.uk

2 HAZARDS IDENTIFICATION

R10 Flammable., R36/38 Irritating to eyes and skin.

Classification Xi;R36/38. R10.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EINICS No.	CAS No.	Content	Classification
1-METHOXY-2-PROPANOL	203-539-1	107-98-2	10 - 30%	R10
3-BUTOXYPROPAN-2-OL	225-878-4	5131-66-8	10 - 30%	Xi;R36/38

The Full Text for all R-Phrases are Displayed in Section 16

4 FIRST-AID MEASURES

INHALATION	Move the exposed person to fresh air at once., Rinse nose and mouth with water., Get medical attention if any discomfort continues.
INGESTION	Remove victim immediately from source of exposure., DO NOT INDUCE VOMITING!, Rinse mouth thoroughly., Drink plenty of water., Get medical attention.
SKIN CONTACT	Remove affected person from source of contamination., Remove contaminated clothing., Rinse the skin immediately with lots of water., Continue to rinse for at least 15 minutes., Get medical attention if irritation persists after washing.
EYE CONTACT	Promptly wash eyes with plenty of water while lifting the eye lids., Get medical attention if any discomfort continues.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA	Use fire-extinguishing media appropriate for surrounding materials.
SPECIAL FIRE FIGHTING PROCEDURES	Use water to keep fire exposed containers cool and disperse vapours.

6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS	Wear necessary protective equipment., Absorb in vermiculite, dry sand or earth and place into containers., Flush with plenty of water to clean spillage area.
ENVIRONMENTAL PRECAUTIONS	Any spillage needs to be contained and not allowed to enter water courses

7 HANDLING AND STORAGE

USAGE PRECAUTIONS	Avoid spilling, skin and eye contact.
USAGE DESCRIPTION	Store in tightly closed original container in a dry, cool and well-ventilated place., Keep in original container.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	TWA - 8 hrs	STEL - 15 min	Notes
1-METHOXY-2-PROPANOL		100 ppm(Sk)	357 mg/m3(Sk)	150 ppm(Sk) 560 mg/m3(Sk)

PROTECTIVE EQUIPMENT



ENGINEERING MEASURES

Provide adequate general and local exhaust ventilation.

HAND PROTECTION

Wear protective gloves.

EYE PROTECTION

Wear approved chemical safety goggles where eye exposure is reasonably probable.

OTHER PROTECTION

General workwear only

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Clear, Liquid
COLOUR	Amber
ODOUR	Solvent.
BOILING POINT (°C)	> 100 C
RELATIVE DENSITY	0.922 - 0.932 @ 20 °C
pH-VALUE, CONC. SOLUTION	N/A
SOLUBILITY	Soluble in water
FLASH POINT (°C)	41 CC (Closed cup).

10 STABILITY AND REACTIVITY

STABILITY	Stable under normal temperature conditions.
CONDITIONS TO AVOID	Avoid excessive heat for prolonged periods of time.
HAZARDOUS DECOMPOSITION PRODUCTS	Fire or high temperatures create:, Toxic gases/vapours/fumes of:, Carbon dioxide (CO ₂), Carbon monoxide (CO).

11 TOXICOLOGICAL INFORMATION

INHALATION	May cause irritation to the respiratory system.
INGESTION	Liquid irritates mucous membranes and may cause abdominal pain if swallowed., May cause stomach pain or vomiting.
SKIN CONTACT	Irritating to skin., Prolonged or repeated exposure may cause severe irritation.
EYE CONTACT	Irritation of eyes and mucous membranes.

12 ECOLOGICAL INFORMATION

ECOTOXICITY	Not classed as Hazardous to the Environment but release to the environment should be avoided.
-------------	---

13 DISPOSAL CONSIDERATIONS

DISPOSAL METHODS	Dispose of waste and residues in accordance with local authority requirements.
------------------	--

14 TRANSPORT INFORMATION

TRANSPORT LABELS



UN NO. ROAD	1993
UK ROAD CLASS	3
UK ROAD PACK GR.	III
ADR CLASS NO.	3
ADR CLASS	Class 3: Flammable liquids.
PROPER SHIPPING NAME	FLAMMABLE LIQUID, NOS (Mixed Glycol Ethers)
UN NO. SEA	1993
IMDG CLASS	3
UN NO. AIR	1993
AIR CLASS	3

15 REGULATORY INFORMATION

LABELLING



Irritant (Xi)

RISK PHRASES	R10 Flammable., R36/38 Irritating to eyes and skin.
SAFETY PHRASES	S2 Keep out of the reach of children, S23 Do not breathe vapour/spray., S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice., S37/39 Wear suitable gloves and eye/face protection., S51 Use only in well-ventilated areas.
STATUTORY INSTRUMENTS	Chemicals (Hazard Information and Packaging) Regulations., Control of Substances Hazardous to Health.
APPROVED CODE OF PRACTICE	Classification and Labelling of Substances and Preparations Dangerous for Supply.
GUIDANCE NOTES	Workplace Exposure Limits EH40., CHIP for everyone HSG(108).

16 OTHER INFORMATION

GENERAL INFORMATION	The following risk phrases relate to the raw materials in the product and not the product itself:-
REVISION DATE	13/04/2006
REV. NO./REPL. SDS GENERATED	4
RISK PHRASES IN FULL	R36/38 Irritating to eyes and skin. R10 Flammable.